



ThyssenKrupp Access



Untrack any other dumbwaiter, the Shuttle uses a special drive train and track system that makes it very easy to install and economical to own. Typical dumbwaiters are built like mini-elevators with complex pulley systems, guide rails and traveling control cables. The Shuttle comes from the factory with the entire drive system pre-installed on the underside of the car, and the car chassis/trolley system pre-installed on a section of the track. Installation isn't much more complicated than connecting sections of track, securing the drive cable to the header, and wiring the controls and Interlocks. In many cases, a full day of installation time can be cut from the process. **That's real savings!**

The Shuttle's drive train system is actually borrowed from our line of stair lifts — a system that has been proven reliable over decades of use. Its benefits are many: The unit rides on a single extruded aluminum track, eliminating the time and expense of assembling complex multi-channel rail systems. Wiring is greatly simplified because the cable-drum drive system is an integral part of the car. The bottom line is you get a reliable dumbwaiter that installs quickly — saving you significantly on the overall cost.

Advantages:

- Fast and easy installation
- Comes with car & drive system premounted on the track
- No pulleys to install
- Cable drive system pre-installed on car
- No complex rail system to assemble
- Simplified wiring (plug-n-play)
- Lower overall cost
- Proven-reliable drive system design
- Made in the USA
- Best warranty: 2-year parts/5-year drive train

Features:

- Car and trolley pre-mounted on track
- Low voltage, automatic operation, call/send controls (24V)
- Low voltage, high quality interlocks
- Standard and final limit switches
- Plug-in temporary bypass control to facilitate installation and maintenance

Options:

- Intermediate car shelf
- Key locks on Call-Sends
- "Car here" indicator
- Remote mount controller package
- Floor mount drive unit (included remote controller package)
- Automatic homing

Specifications:

Car inner dimensions -

- 20" w x 20" d x 30" h (standard) 24" w x 24" d x 30" h (optional) 30" w x 30" d x 36" h (optional) (Custom sizes available up to 30" x 30" x 36")
- Finish Car interior and doors feature a durable ivory powder coat finish. Stainless steel car interior also available.
- Capacity 100 lbs.
- (Available up to 200 lbs.)
- Travel Up to 28'.
- Track Extruded aluminum
- Stops 2, 3 or 4
- Speed 20 feet per minute
- Hoistway door interlocks
- G.A.L. interlocks or optional electromechanical interlocks
- Controls Push button call-send controls, 24 volt
- Cable Aircraft cable rated at 1,800 lbs. breaking strength
- Motor 1/2 HP, 90 VDC motor
- Warranty 2 year warranty on parts and 5 years on the drive train
- Electric supply 115 VAC grounded circuit
- Designed to meet ASME standards

ShuttleTM DUMBWAITER

Simplified wiring Simplified controls Simplified drive system Simplified installation Simplified maintenance

Simply the best value



Electric motor, cabledrum drive system and limit switches are preinstalled under car.

Car and drive system chassis come preinstalled on a short section of track. Extra lengths of track splice together with ease.

High-quality G.A.L. interlocks help assure safe, secure, and reliable performance.





ThyssenKrupp Access Corp. 4001 East 138th Street Grandview, MO 64030

800.829.9760 www.tkaccess.com

